

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

S.A.N. Siliconespray 30%

Product no.

-

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Lubricant

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Unipak A/S
Marktoften 3C
8464 Galten
Denmark

Tel: +45 8626 1177

E-mail

sales@unipak.dk

SDS date

2018-08-27

SDS Version

3.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229

See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. (H222)

Pressurised container: May burst if heated. (H229)

Safety statement(s)

General Prevention	- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210). Do not spray on an open flame or other ignition source. (P211). Do not pierce or burn, even after use. (P251). Avoid breathing spray. (P261). Use only outdoors or in a well-ventilated area. (P271).
Response Storage	- Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412).
Disposal	-

Identity of the substances primarily responsible for the major health hazards

Not applicable

2.3. Other hazards

Not applicable

Additional labelling

Not applicable

Additional warnings

Not applicable

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME:	butane
IDENTIFICATION NOS.:	CAS-no: 106-97-8 EC-no: 203-448-7 REACH-no: 01-2119474691-32 Index-no: 601-004-00-0
CONTENT:	20-70%
CLP CLASSIFICATION:	Flam. Gas 1 H220
NAME:	and isobutane
IDENTIFICATION NOS.:	CAS-no: 75-28-5 EC-no: 200-857-2 REACH-no: 01-2119485395-27 Index-no: 601-004-00-0
CONTENT:	20-70%
CLP CLASSIFICATION:	Flam. Gas 1 H220
NAME:	propane
IDENTIFICATION NOS.:	CAS-no: 74-98-6 EC-no: 200-827-9 REACH-no: 01-2119486944-21 Index-no: 601-003-00-5
CONTENT:	20-70%
CLP CLASSIFICATION:	Flam. Gas 1 H220

(*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service (dial 111, 24 h service).
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses and open eyes widely. Flush eyes with water or saline water (20-30°C) for at least 15 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Rinse with water until the pain stops then continue to rinse for a further 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

4.3. Indication of any immediate medical attention and special treatment needed

Nothing special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, storage of tobacco, consumption and storage of food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Storage temperature

5 – 45 °C

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

butane

Long-term exposure limit (8-hour TWA reference period): 600 ppm | 1450 mg/m³

Short-term exposure limit (15-minute reference period): 750 ppm | 1810 mg/m³

DNEL / PNEC

No data available

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Observe general occupational hygiene standards.

Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

Recommended: A. Class 1 (low capacity). Brown

Skin protection

Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester. Chemical resistant suit with helmet/hood (Type 4, 5, 6 Category III) is recommended for spray applications.

Hand protection

Recommended: Nitrile rubber

Eye protection

Wear face shield alternatively safety glasses with side shields.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Aerosol
Colour	Colourless
Odour	None
Odour threshold (ppm)	No data available.
pH	No data available.
Viscosity (40°C)	No data available.
Density (g/cm ³)	No data available.
Phase changes	
Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.

Data on fire and explosion hazards

Flash point (°C)

No data available.

Ignition (°C)

No data available.

Auto flammability (°C)

No data available.

Explosion limits (% v/v)

No data available.

Explosive properties

No data available.

Solubility

Solubility in water

Insoluble

n-octanol/water coefficient

No data available.

9.2. Other information

Solubility in fat (g/L)

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

Nothing special

10.4. Conditions to avoid

Avoid static electricity. Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: propane

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: 658 mg/l

Substance: propane

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: 1237 mg/l air 2h

Substance: and isobutane

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: 1237 mg/l air 2h

Substance: butane

Species: Rat

Test: LC50

Route of exposure: Inhalation

Result: 1237 mg/L 2h

Skin corrosion/irritation

No data available.

Serious eye damage/irritation

No data available.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

Nothing special

SECTION 12: Ecological information

12.1. Toxicity

Substance: propane
Species: Fish
Test: LC50
Duration: 96 h
Result: 27,98 - 49,9 mg/l

Substance: propane
Species: Daphnia
Test: LC50
Duration: 48 h
Result: 14,22 - 46,6 mg/l

Substance: propane
Species: Algae
Test: EC50
Duration: 96 h
Result: 7,71 - 11,89 mg/l

Substance: and isobutane
Species: Fish
Test: LC50
Duration: 96 h
Result: 24,11 - 147,54 mg/l

Substance: and isobutane
Species: Algae
Test: EC50
Duration: 96 h
Result: 7,71 - 19,37 mg/l

Substance: and isobutane
Species: Daphnia
Test: LC50
Duration: 48 h
Result: 14,22 - 69,43 mg/l

Substance: butane
Species: Fish
Test: LC50
Duration: 96h
Result: 27,98 mg/L

Substance: butane
Species: Algae
Test: EC50
Duration: 96h
Result: 7,71 mg/L

Substance: butane
Species: Daphnia
Test: LC50
Duration: 48h
Result: 14,22 - 69,43 mg/L

Substance: butane
Species: Fish
Test: LC50
Duration: 96h

According to EC-Regulation 2015/830

Result: 24,11 - 147,54 mg/l

Substance: butane
Species: Algae
Test: EC50
Duration: 96h
Result: 7,71 - 19,37 mg/l

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
propane	Yes	385,5 h, predates, OECD.	100 %
and isobutane	Yes	385,5 h, predates, OECD.	100 %
butane	Yes	385,5 h, predates, OECD.	100%

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
No data available.			

12.4. Mobility in soil

butane: Log Koc= 0,941571, Calculated from LogPow (High mobility potential.).

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

Nothing special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

Waste

EWC code

16 05 04

gases in pressure containers (including halons) containing dangerous substances

Specific labelling

-

Contaminated packing

Contaminated packaging must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 – 14.4

This product is within scope of the regulations of transport of dangerous goods.

ADR/RID

14.1. UN number	1950
14.2. UN proper shipping name	AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es)	2.1
14.4. Packing group	-
Notes	-
Tunnel restriction code	-

IMDG

UN-no.	1950
Proper Shipping Name	AEROSOLS, FLAMMABLE
Class	2.1
PG*	-
EmS	F-D, S-U
MP**	-
Hazardous constituent	-

IATA/ICAO

UN-no.	1950
Proper Shipping Name	AEROSOLS, FLAMMABLE
Class	2.1
PG*	-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

-

Demands for specific education

-

Additional information

Not applicable

Seveso

Seveso III Part 1: P3a

Sources

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

EC regulation 1907/2006 (REACH).

The Control of Major Accident Hazards (COMAH) Regulations 2015.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H220 - Extremely flammable gas.

The full text of identified uses as mentioned in section 1

-

Additional label elements



Other

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of physical hazards has been based on experimental data.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.